

# Technical Note

## Reference: AM 307

### ANTIBEADING

Version 01  
April 2017  
Page 1/1

---

**Type:** Suspension of aluminum oxide in a composition of non-aromatic hydrocarbons and water.

**Physical form:** Yellow liquid paste.

**Special properties:** Cleaner / Antibeading

**Description:** To be applied after the Polymer treatment to avoid Beading.

**How to use:** Shake the container vigorously before applying to the surfaces. Using a soft cloth, apply small quantity of product on an area not greater than 50 x50 cm. Do not apply on hot surfaces. Use a variable speed circular polisher, equipped with a sponge pad. Start the Polisher at 1500rpm. Polish the 50 x50 cm area by applying a reasonable amount of pressure on the polisher and by increasing the speed gradually to 2000 rpm (maximum). As the product dissipates reduce the pressure applied to the polisher. Proceed by changing the sponge pad on the polisher to a soft foam pad and dry polish the 50 x 50 cm area in order to remove the excess residue. The product should be cleaned off using a wet soft cloth or sponge.

**Handling precautions:** Before handling, read product information safety data sheets and container labels for safe use.

**Storage information:** PERMAGARD products need to be stored between 50°F (10°C) and 77°F (25°C) and protected from light.

#### **Shipping information:**

Packaging: 6 bottles of 1L per box

Weight: 9 kg per box

Dimensions: 25x18x26 cm

Harmonized code for Customs: 3405.30.00.00